



McCoy Miller

Global Appeal.



Ford E-450



Chevy G4500

Driven for Quality and Value

Medic 163 & 170 • Type III Ambulance

CHASSIS

Chevy CG33803 Cutaway

- 14,200 GVWR
- 159" Wheel Base
- 6.6L Diesel (dual alternators)
- 100" CA – Dual Rear Wheels

Ford E-450 Cutaway

- 14,200 GVWR
- 158" Wheel Base
- 6.8L V-10 Gas Engine (single 225 amp alternator)

STANDARD FEATURES

Body

- All aluminum construction
- Fully welded tubular structure on 12" centers
- Side body crash bar
- Modular Body: 170"L x 98"W x 72" H or 163"L x 98"W x 72"H
- .125 Body Side Skin: 1 piece sidewall
- Crown rolled roof to inhibit water pooling
- Rear Bumper: Steel frame with ADP covering and flip-up center to facilitate loading
- Front Wall: 9" recess for full driver seat travel
- O2 Storage: Streetside front wall
- Seven exterior storage compartments

Warning Lights & Sirens

- Flasher: Vanner 3860 GCPE
- Intersection Lights: Two Whelen 700 Series Red LED
- Grille Lights: Two Whelen 500 Series Red LED (Ford)
- Grille Lights: Two Whelen 700 Series Red LED (GM)
- Warning Lights: Ten Whelen 900 Series Halogens
- Load Lights: Two Whelen 900 Series
- Scene Lights: Four Whelen 900 Series
- Siren: Whelen WS-295HFSA7 dual tone
- Speakers: Two CPI with 100w wall speakers
- Back-Up Alarm: 97 Db with momentary cutoff
- ICC LED marker lights

Environmental

- AC-Heat System: 650 CFM blower, 32,000 BTU heat, 35,000 BTU cool
- Vent Power: Marine style with 3-speed fan
- Insulation: 3" Fiberglas bats
- O2 Cradle for "M" or "H" tanks

Interior

- Height: 72"
- Flooring: Loncoin II Fleckstone with 3" rolled up sidewall and recessed
- Dome Lights: Eight dual element, halogen, two rows of four each, switched separately
- Spotlight: One, 400,000CP hand-held light with momentary switch, hard wired to OEM dash
- Cot Mount: Ferno-Washington 175-4
- ALS Cabinet: Two large cabinets with 3/8" hinged Plexiglas doors
- Hazardous Waste/Sharps Disposal: Stainless steel A Bar at the head of the squad bench
- Aspirator: Rico RS-4X disposable
- IV Holders: Two dual cast, swing down rubber holders with Velcro retaining straps

Door

- Improved Design: Reduced welding, heat distortion and body fill to enhance overall appearance
- HD Extruded Door Jams: Key locked and welded
- HD Extruded Door Frames: .125 pan-formed skin
- Integrated Door Seal: Reduces wear on seal and eliminates outer contamination of doors, compartments and modules
- Door Liners: .125 aluminum with durable Multispec finish, attached with 10-24 stainless steel screws into rivnuts
- Magnetic door jam switches
- Latches: TriMark automotive style

Power Distribution/Electrical

- Commander 357 electronic master switch with timer
- Etched-Trace Power Circuits: HD-3 oz.
- Etched-Trace Control Circuits: HD-3 oz.
- Marine Grade High Current Switches: Replaceable, for milliamp circuit
- Door Open Circuits: Magnetic/LED diagnostic circuit
- HD Machine Crimped Harness: Pull and load tested
- Inverter: Prewired for 1000W inverter
- Clock: LED in rear control panel

Warranty

- Body: 4 Year/48,000 mile
- Structure: 15 Year
- Electrical: 6 Year/72,000 mile
- Paint: 7 Year (PPG Delfleet paint product system)



Optional Interior Trim Packages Available



Optional V-Mux Electrical System Available



Optional Ducted HVAC Available

Interior Streetside



Interior Curbside



Exterior



Exterior



MCCOY MILLER
Global Appeal



www.mccoymiller.com